

www.arpnjournals.com

FOUR-BAR MECHANISM'S ROTATION CENTER DETERMINATION USING NATURAL COORDINATES

Neider Nadid Romero^{1,2}, Edwin B. Rua Ramírez³ and Gonzalo G. Moreno Contreras^{4,2} ¹Departament of Mechanical Engineering, Pontifical Bolivarian University, Montería, Colombia ²Departament of Mechanical Engineering, Federal University of Santa Catarina, Florianopolis, Brazil ³Departament of Mechanical Engineering, Santo Thomas University, Tunja, Colombia ⁴Departament of Mechanical Engineering, University of Pamplona, Pamplona, Colombia E-Mail: <u>gmoren@unipamplona.edu.co</u>

ABSTRACT

In this paper the use of natural coordinates for the analytical determination of the center of rotation of four-bar mechanisms is proposed. The natural coordinates are mostly Cartesian coordinates located in the kinematic pairs or in points of interest of the mechanism, where the main advantage of their use is that angular parameters and trigonometric functions can be disregarded, which facilitates the understanding of the modeling, in addition it is not necessary to use trigonometric functions. This tecnique allow to reduce the computational cost in a great way, optimizing problems where the rotation center has to be calculated many times. To achieve this goal, the problem is described and formulated in a robust way using natural coordinates and operating within the body of complex numbers. Then, to deal with the present problem, the mechanism's kinematics position in natural coordinates is modeled and computing and with the obtained equations, a program is implemented in MATLAB® to show the curve described by the rotation centers of links, which is fundamental for the optimal design of polycentric mechanisms.

Keywords: four bar mechanism, rotation center, natural coordinates.

1. INTRODUCTION

The center of rotation of a plane mechanism refers to a common point of two bodies not necessarily connected that share the same velocity [1]. In this case the center of rotation refers to that formed by the coupler and the fixed link, known as the zero-speed center of rotation. For spatial mechanisms, the rotation center's analogue to the center of rotation is the instantaneous axis of rotation, which is the basis of the infinitesimal screw theory [2-4]. The determination of the curve that describes the center of rotation is of vital importance in the optimal design of mechanisms for lower limb prostheses, where the mechanism's center of rotation must approach the curve described by the knee's center of rotation, this curve is known as the poloid [5-7]. Traditionally, the position analysis of a four-bar mechanism is based on the vectorloop closing equations, and therefore the equations that determine the center of rotation are in terms of angular parameters, in addition to trigonometric functions, as is done in Amador [8] and Radcliffe [9].

Natural coordinates were first introduced by De Jalon & Bayo [10], which are mostly Cartesian coordinates located in kinematic pairs or points of interest. The main advantage of using natural coordinates to model mechanisms is that the use of angles and the trigonometric functions can be disregarded, which facilitates the modeling and implementation of the obtained equations [11]. In literature, work on natural coordinates is not very abundant; however, there are several important papers on the subject which stand out: Núñez [12], where natural coordinates are used to model vehicle steering mechanisms up to eight bars; in this paper the kinematic equations are solved numerically. In Núñez [13], the problem of position of a four-bar mechanism using natural coordinates was solved analytically. In Rojas & Thomas [14], a general procedure is presented to solve the positioning problem of plane mechanisms, using the concept of bilateration that focuses in two given points to determine the third point of a triangle.

The general objective of this paper is to determine in an analytical way the zero-speed center of rotation in a four-bar mechanism using natural coordinates. The equations obtained are implemented in MATLAB® to show the curve described by the center of rotation, which is of vital importance in many applications where mechanism's stability depends directly on the rotation center.

2. POSITIONING KINEMATICS USING NATURAL COORDINATES

Figure-1 displays the four-bar mechanism's modeling using natural coordinates, where the natural coordinate vector is given by:

$$q = \begin{bmatrix} C \\ D \end{bmatrix} = \begin{bmatrix} C_x \\ C_y \\ D_x \\ D_x \end{bmatrix}$$
(1)

ISSN 1819-6608

www.arpnjournals.com

©2006-2020 Asian Research Publishing Network (ARPN). All rights reserved.



VOL. 15, NO. 22, NOVEMBER 2020

Figure-1. Four-bar mechanism's modeling using natural coordinates. Source Author

Where C and D corresponds to the mechanism's coupler kinematic pair coordinates. A and B are the fixed pair coordinates.

То determine the natural coordinates, the procedure developed by Núñez [13] was used; this one is based on triangulation, which consists of determining a point of a triangle by knowing two points of said triangle. From the triangle CBD, the points C and B are known, the point *C* is determined by:

$$C = A + \begin{bmatrix} a\cos\varphi\\a\sin\varphi \end{bmatrix} = \begin{bmatrix} A_x + a\cos\varphi\\A_y + a\sin\varphi \end{bmatrix}$$
(2)

Making the distance between *C* and *B* be,

$$s = \left\| B - C \right\| \tag{3}$$

The following relations can be written:

$$l = \frac{b^2 + s^2 - c^2}{2s}$$
(4)

$$h = t\sqrt{b^2 - l^2} \tag{5}$$

Where t takes values of -1 or 1 that represent the four-bar mechanism's two configurations. From Figure-1 it can be clearly appreciated that D point can be determined by:

$$D = C + \frac{l}{s} \left(B - C \right) + \frac{h}{s} R \left(B - C \right)$$
(6)

$$R = \begin{bmatrix} 0 & -1 \\ 1 & 0 \end{bmatrix}$$
(7)

where R corresponds to a ninety-degree rotation of the vector (B - C) The Eq. (6) can be written as follows:

$$D = C + \left[\frac{l}{s}e + \frac{h}{s}R\right](B - C)$$
(8)

where:

$$\begin{bmatrix} \frac{l}{s}e + \frac{h}{s}R \end{bmatrix} = \begin{bmatrix} \frac{l}{s} & -\frac{h}{s} \\ \frac{h}{s} & \frac{l}{s} \end{bmatrix} = N$$
(9)

where e is the identity matrix. So, point D is determined by:

$$D = C + N(B - C) \tag{10}$$

In this way the problem of positioning of four bars is solved, making use of natural coordinates. The obtained equations are simple and easily implemented in a computer. For more information on the natural coordinates, consult Avello [11].

3. ROTATION CENTER DETERMINATION

To determine rotation center I (Figure-1), the following relation can be written,

$$I = A + \lambda u = B + \beta v \tag{11}$$

where λ , β are scalars are *u*, *v* are unitary vectors determined by:

$$u = \frac{(C-A)}{\|C-A\|} \tag{12}$$

$$v = \frac{(D-B)}{\|D-B\|} \tag{13}$$

From equations (11) it is understood that,

$$\lambda u - \beta v = (B - A) \tag{14}$$

written in matrix form as,

$$\begin{bmatrix} u_{x} & -v_{x} \\ u_{y} & -v_{y} \end{bmatrix} \begin{bmatrix} \lambda \\ \beta \end{bmatrix} = \begin{bmatrix} (B_{x} - A_{x}) \\ (B_{y} - A_{y}) \end{bmatrix}$$
(15)

and applying Cramer's rule it can be appreciated that,

(16)

www.arpnjournals.com

$$\lambda = \frac{\begin{vmatrix} (B_x - A_x) & -v_x \\ (B_y - A_y) & -v_y \end{vmatrix}}{\begin{vmatrix} u_x & -v_x \\ u_y & -v_y \end{vmatrix}}$$

.

$$\lambda = \frac{\begin{vmatrix} u_x & (B_x - A_x) \\ u_y & (B_y - A_y) \end{vmatrix}}{\begin{vmatrix} u_x & -v_x \\ u_y & -v_y \end{vmatrix}}$$
(17)

If, the denominator is equal to zero, the vectors u and v are parallel, and the rotation center will hence tend to infinity. In this way we can determine the center of rotation of a four-bar mechanism for any input angle φ .

4. RESULTS

.

Obtained equations were implemented in the numeric software MATLAB®, for a four-bar mechanism with the dimensions shown in Table-1.

 Table-1. Four-Bar Mechanism Dimensions in Centimeters.

а	b	с	A_{x}	A_{y}	B_{x}	B_{y}
1.5	3	2	0	0	4.5	0

Figure-2 shows the path described by the center of rotation, where the entry angle is in the range - $20 \le \varphi \le$ 100. The center of rotation for angles outside this range tends to infinity or does not exist because assembly of the mechanism is not possible.



Figure-2. Curve described by the rotation center for t =1. Source Author



Figure-3. Curve described by the rotation center for t =-1. Source Author

The curve described by the center of rotation is shown in Figure-3, where the angle of entry is in the range $-100 \le \varphi \le 30^{\circ}$.

5. DISCUSSIONS

The equations obtained and implemented in MATLAB® disposes of trigonometric functions, which facilitates the interpretation of the model and decreases the computational cost. The method proposed here for the rotation center's determination can be generalized, and therefore be applied to more complex mechanisms. The generalization of this method is intended to be developed in future papers. It should also be mentioned that in the design of lower limb prosthesis, the center rotation is required to describe a given curve, this being one of the rotation center's most important applications [6].

6. CONCLUSIONS

In this paper, it was possible to analytically determine the four-bar mechanism's coupler center of rotation using natural coordinates.

The equations obtained are simple and compact, which makes them ideal to be implemented in a computer.

By the time this paper was written, the use of natural coordinates for the calculation of rotation centers in a mechanism was never described, making it the first paper to make use natural coordinates for that purpose.

The use of angular coordinates is discarded, which facilitates the understanding of the modeling, in addition it is not necessary to use trigonometric functions, which allow to reduce the computational cost in a great way, optimizing problems where the rotation center has to be calculated many times.

REFERENCES

 Norton R. L. & Wang S. S. L. 2004. Design of machinery: an introduction to the synthesis and analysis of mechanisms and machines. McGraw-Hill Higher Education.

www.arpnjournals.com

- [2] Davidson J. K., Hunt K. H. & Hunt K. H. 2004. Robots and screw theory: applications of kinematics and statics to robotics. Oxford University Press on Demand.
- [3] Gallardo-Alvarado J., Rodríguez-Castro R., Pérez-González L. & Aguilar-Nájera C. R. 2013. Análisis cinemático de un manipulador paralelo plano mediante la teoría de tornillos infinitesimales. Científica. 17(4).
- [4] G. Moreno, L. Nicolazzi, R.S. Vieira, D. Martins. 2017. Suspension and tyres: the stability of heavy vehicles, International Journal of Heavy Vehicle Systems. 24(4): 305-326. doi:10.1504/IJHVS.2017.10007635, 2017.
- [5] Jin D., Zhang R., Dimo H. O., Wang R. & Zhang J. 2003. Kinematic and dynamic performance of prosthetic knee joint using six-bar mechanism. Journal of rehabilitation research and development. 40(1): 39-48.
- [6] Torfason L. E. & Hobson D. A. 1973. Computer optimization of polycentric prosthetic knee mechanisms. In Proceedings of the Third Applied Mechanisms Conference.
- [7] Össur Iberia. 2016. Össur Soluciones Protésicas.
- [8] Amador B. T., Torrealba R. R., Rojas M., Cappelletto J. & Müller-Karger C. M. 2012. Methodology to Gauge a Four-Bar Linkage Prosthetic Knee Mechanism Based on Gait Analysis and Genetic Algorithms. Revista Ingeniería Biomédica. 6(11): 30-45.
- [9] Radcliffe C. W. 1994. Four-bar linkage prosthetic knee mechanisms: kinematics, alignment and prescription criteria. Prosthetics and orthotics international. 18(3): 159-173.
- [10] De Jalon J. G. & Bayo E. 2012. Kinematic and dynamic simulation of multibody systems: the realtime challenge. Springer Science & Business Media.
- [11] Avello A. 2014. Teoría de Máquinas 2nd ed., Pamplona, España.
- [12] Núñez, N. N. R. 2014. Síntese estrutural e otimização dimensional de mecanismos de direção. Master thesis. Federal University of Santa Catarina-Brazil.
- [13] Núñez N. N. R. 2016. Análisis de posición de un mecanismo de cuatro barras utilizando coordenadas

naturales. Revista Iberoamericana de Ingeniería Mecánica. 20(2): 83-90.

[14] Rojas N. & Thomas F. 201. Distance-based position analysis of the three seven-link Assur kinematic chains. Mechanism and Machine Theory. 46(2): 112-126.